Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00185
County: Idaho
Funct Class: R Principal Arterial - Other
Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
Daily Factor Grp: 5
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 8

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	205	184	1	3	4	1	4	18	24	2	2	6	0
	Flex	.00	.00	.00	.36	.26	.41	.18	.24	.96	.41	.03	.56	1.44	0.00
	Rigid	.00	.00	.00	.56	.28	.51	.18	.26	1.40	.79	.04	.56	2.48	0.00
	GVW	1.3	3.9	4.2	19.9	15.5	25.5	20.0	17.8	47.9	62.5	21.6	45.8	75.4	0.0
E	Num	2	99	91	1	2	2	1	3	10	12	1	1	3	0
	Flex	.00	.00	.00	.51	.23	.29	.16	.31	1.44	.52	.04	.65	1.46	0.00
	Rigid	.00	.00	.00	.82	.25	.38	.15	.35	2.15	.76	.05	.67	2.47	0.00
	GVW	1.1	4.1	4.0	24.0	14.5	21.8	19.0	20.0	57.6	43.8	21.3	48.7	57.0	0.0
W	Num	2	106	92	1	2	2	1	3	8	12	2	1	4	0
	Flex	.00	.00	.00	.04	.30	.47	.18	.08	.34	.30	.02	.85	.72	0.00
	Rigid	.00	.00	.00	.04	.30	.58	.18	.08	.43	.77	.02	.85	1.32	0.00
	GVW	1.5	3.8	4.4	11.8	15.9	29.0	20.6	15.2	35.9	75.7	18.6	44.6	78.3	0.0
E Lane1	Num	2	99	91	1	2	2	1	3	10	12	1	1	3	0
	Flex	.00	.00	.00	.51	.23	.29	.16	.31	1.44	.52	.04	.65	1.46	0.00
	Rigid	.00	.00	.00	.82	.25	.38	.15	.35	2.15	.76	.05	.67	2.47	0.00
	GVW	1.1	4.1	4.0	24.0	14.5	21.8	19.0	20.0	57.6	43.8	21.3	48.7	57.0	0.0
W Lane1	Num	2	106	92	1	2	2	1	3	8	12	2	1	4	0
	Flex	.00	.00	.00	.04	.30	.47	.18	.08	.34	.30	.02	.85	.72	0.00
	Rigid	.00	.00	.00	.04	.30	.58	.18	.08	.43	.77	.02	.85	1.32	0.00
	GVW	1.5	3.8	4.4	11.8	15.9	29.0	20.6	15.2	35.9	75.7	18.6	44.6	78.3	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 05/08/2025 10:59 AM

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00185
County: Idaho
Funct Class: R Principal Arterial - Other
Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
Daily Factor Grp: 5
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 8

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 05/08/2025 10:59 AM