

Idaho Transportation Department

Monthly WIM Distribution for Sep-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	20	2,357	1,224	19	120	165	4	89	657	19	15	9	13	0
	Flex	.02	.00	.00	.57	.27	.33	.30	.14	.75	.64	2.23	.86	1.41	0.00
	Rigid	.04	.00	.00	.77	.27	.58	.68	.16	1.35	1.43	2.22	1.19	2.50	0.00
	GVW	12.1	2.6	4.7	37.6	17.9	33.1	43.3	23.2	60.0	71.7	65.9	63.9	84.7	0.0
N	Num	6	1,163	599	7	46	66	1	36	300	10	8	4	7	0
	Flex	.02	.00	.00	.83	.36	.42	.40	.19	1.04	.85	2.47	.98	1.67	0.00
	Rigid	.04	.00	.00	1.19	.36	.78	.90	.23	1.94	1.99	2.44	1.13	3.31	0.00
	GVW	12.5	2.6	4.7	42.5	18.8	34.4	47.0	23.9	64.6	77.3	70.1	59.3	87.9	0.0
S	Num	14	1,194	624	13	74	99	3	54	357	9	8	6	5	0
	Flex	.02	.00	.00	.44	.22	.26	.31	.11	.51	.40	1.54	.67	1.04	0.00
	Rigid	.04	.00	.00	.55	.22	.44	.69	.12	.87	.82	1.56	1.06	1.51	0.00
	GVW	11.9	2.6	4.6	34.9	17.3	32.1	43.5	22.8	56.2	65.4	57.6	63.6	80.8	0.0
N Lane1	Num	6	1,163	599	7	46	66	1	36	300	10	8	4	7	0
	Flex	.02	.00	.00	.83	.36	.42	.40	.19	1.04	.85	2.47	.98	1.67	0.00
	Rigid	.04	.00	.00	1.19	.36	.78	.90	.23	1.94	1.99	2.44	1.13	3.31	0.00
	GVW	12.5	2.6	4.7	42.5	18.8	34.4	47.0	23.9	64.6	77.3	70.1	59.3	87.9	0.0
S Lane1	Num	14	1,194	624	13	74	99	3	54	357	9	8	6	5	0
	Flex	.02	.00	.00	.44	.22	.26	.31	.11	.51	.40	1.54	.67	1.04	0.00
	Rigid	.04	.00	.00	.55	.22	.44	.69	.12	.87	.82	1.56	1.06	1.51	0.00
	GVW	11.9	2.6	4.6	34.9	17.3	32.1	43.5	22.8	56.2	65.4	57.6	63.6	80.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9