

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	23	2,018	1,114	17	100	163	5	81	637	24	17	9	13	0
	Flex	.02	.00	.00	.73	.21	.40	.26	.16	.91	.57	1.27	.92	1.29	0.00
	Rigid	.05	.00	.00	.99	.20	.72	.59	.19	1.67	1.31	1.23	1.27	2.05	0.00
	GVW	13.3	2.5	4.4	40.8	17.2	35.0	43.6	24.4	63.9	74.4	58.7	65.6	87.0	0.0
N	Num	8	977	516	6	38	64	3	32	284	13	8	4	7	0
	Flex	.02	.00	.00	.74	.19	.38	.17	.18	.86	.58	1.55	.90	1.21	0.00
	Rigid	.04	.00	.00	1.06	.19	.68	.43	.22	1.57	1.33	1.49	1.12	2.04	0.00
	GVW	12.1	2.5	4.3	41.3	16.7	34.3	38.4	25.6	62.5	73.5	63.8	62.7	86.5	0.0
S	Num	15	1,042	598	11	62	99	3	49	353	11	9	5	5	0
	Flex	.02	.00	.00	.71	.22	.41	.31	.14	.96	.58	.97	.87	1.40	0.00
	Rigid	.05	.00	.00	.93	.21	.75	.69	.16	1.74	1.30	.94	1.28	2.08	0.00
	GVW	13.8	2.6	4.5	40.0	17.6	35.5	48.0	23.7	65.1	74.8	53.5	65.2	85.0	0.0
N Lane1	Num	8	977	516	6	38	64	3	32	284	13	8	4	7	0
	Flex	.02	.00	.00	.74	.19	.38	.17	.18	.86	.58	1.55	.90	1.21	0.00
	Rigid	.04	.00	.00	1.06	.19	.68	.43	.22	1.57	1.33	1.49	1.12	2.04	0.00
	GVW	12.1	2.5	4.3	41.3	16.7	34.3	38.4	25.6	62.5	73.5	63.8	62.7	86.5	0.0
S Lane1	Num	15	1,042	598	11	62	99	3	49	353	11	9	5	5	0
	Flex	.02	.00	.00	.71	.22	.41	.31	.14	.96	.58	.97	.87	1.40	0.00
	Rigid	.05	.00	.00	.93	.21	.75	.69	.16	1.74	1.30	.94	1.28	2.08	0.00
	GVW	13.8	2.6	4.5	40.0	17.6	35.5	48.0	23.7	65.1	74.8	53.5	65.2	85.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9