

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	18	2,597	1,303	18	124	328	4	103	424	17	12	7	7	0
	Flex	.04	.00	.00	.69	.29	.45	.42	.10	.99	.77	1.50	.79	1.45	0.00
	Rigid	.08	.00	.00	.97	.30	.83	1.05	.11	1.78	1.77	1.56	1.14	2.40	0.00
	GVW	12.9	2.7	4.5	36.8	17.5	34.4	46.6	20.5	60.7	72.4	59.3	61.1	86.5	0.0
N	Num	5	1,308	644	8	53	144	1	46	204	8	7	3	4	0
	Flex	.05	.00	.00	.79	.39	.44	.44	.12	1.13	.93	1.93	.99	2.05	0.00
	Rigid	.10	.00	.00	1.14	.39	.80	1.15	.13	2.01	2.19	1.97	1.26	3.56	0.00
	GVW	11.6	2.6	4.5	39.7	18.6	33.8	44.9	20.3	62.6	74.6	65.4	63.5	94.8	0.0
S	Num	13	1,289	660	10	71	185	4	57	220	9	7	4	4	0
	Flex	.04	.00	.00	.62	.22	.47	.39	.08	.85	.59	1.04	.61	1.08	0.00
	Rigid	.08	.00	.00	.82	.22	.88	.96	.09	1.54	1.30	1.04	1.05	1.56	0.00
	GVW	13.5	2.7	4.4	34.5	16.6	35.0	46.4	20.5	58.7	69.3	52.1	58.9	80.1	0.0
N Lane1	Num	5	1,308	644	8	53	144	1	46	204	8	7	3	4	0
	Flex	.05	.00	.00	.79	.39	.44	.44	.12	1.13	.93	1.93	.99	2.05	0.00
	Rigid	.10	.00	.00	1.14	.39	.80	1.15	.13	2.01	2.19	1.97	1.26	3.56	0.00
	GVW	11.6	2.6	4.5	39.7	18.6	33.8	44.9	20.3	62.6	74.6	65.4	63.5	94.8	0.0
S Lane1	Num	13	1,289	660	10	71	185	4	57	220	9	7	4	4	0
	Flex	.04	.00	.00	.62	.22	.47	.39	.08	.85	.59	1.04	.61	1.08	0.00
	Rigid	.08	.00	.00	.82	.22	.88	.96	.09	1.54	1.30	1.04	1.05	1.56	0.00
	GVW	13.5	2.7	4.4	34.5	16.6	35.0	46.4	20.5	58.7	69.3	52.1	58.9	80.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9