

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2024

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	1,697	857	16	80	582	6	50	146	18	1	3	3	0
	Flex	.06	.00	.00	.62	.14	.50	.31	.11	1.05	.62	.93	1.07	1.61	0.00
	Rigid	.13	.00	.00	.89	.14	.94	.76	.12	1.82	1.42	1.01	1.45	3.29	0.00
	GVW	14.1	2.4	4.0	37.0	15.3	37.7	49.1	22.6	63.8	72.5	52.5	70.2	105.5	0.0
N	Num	4	850	420	8	37	259	2	24	62	11	1	2	2	0
	Flex	.05	.00	.00	.64	.15	.45	.33	.10	.93	.55	1.13	1.44	2.32	0.00
	Rigid	.11	.00	.00	.90	.15	.84	.84	.11	1.58	1.25	1.19	2.05	4.59	0.00
	GVW	12.8	2.5	4.1	36.6	15.9	36.6	49.2	22.1	60.5	69.7	56.2	76.6	117.7	0.0
S	Num	5	847	437	8	43	323	4	26	84	7	1	2	2	0
	Flex	.07	.00	.00	.56	.13	.53	.29	.11	1.14	.69	.89	.81	1.09	0.00
	Rigid	.15	.00	.00	.83	.13	1.02	.70	.13	1.99	1.64	.95	1.12	2.41	0.00
	GVW	15.2	2.4	3.9	36.4	14.9	38.4	48.8	23.1	66.3	75.9	52.7	66.0	96.5	0.0
N Lane1	Num	4	850	420	8	37	259	2	24	62	11	1	2	2	0
	Flex	.05	.00	.00	.64	.15	.45	.33	.10	.93	.55	1.13	1.44	2.32	0.00
	Rigid	.11	.00	.00	.90	.15	.84	.84	.11	1.58	1.25	1.19	2.05	4.59	0.00
	GVW	12.8	2.5	4.1	36.6	15.9	36.6	49.2	22.1	60.5	69.7	56.2	76.6	117.7	0.0
S Lane1	Num	5	847	437	8	43	323	4	26	84	7	1	2	2	0
	Flex	.07	.00	.00	.56	.13	.53	.29	.11	1.14	.69	.89	.81	1.09	0.00
	Rigid	.15	.00	.00	.83	.13	1.02	.70	.13	1.99	1.64	.95	1.12	2.41	0.00
	GVW	15.2	2.4	3.9	36.4	14.9	38.4	48.8	23.1	66.3	75.9	52.7	66.0	96.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2024

Site names: 00192  
 County: Twin Falls  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9