

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	1,950	983	17	105	581	6	74	165	19	2	4	4	0
	Flex	.07	.00	.00	.75	.24	.51	.23	.11	1.05	.63	.87	1.04	1.49	0.00
	Rigid	.14	.00	.00	1.00	.24	.98	.61	.12	1.81	1.48	.96	1.44	3.04	0.00
	GVW	14.1	2.5	4.2	37.4	16.8	37.8	45.5	21.8	63.0	72.9	52.6	68.1	101.1	0.0
N	Num	4	998	505	10	58	268	3	43	73	10	1	2	2	0
	Flex	.02	.00	.00	.82	.31	.46	.25	.11	.99	.60	.73	1.12	2.01	0.00
	Rigid	.04	.00	.00	1.09	.31	.87	.69	.12	1.65	1.40	1.00	1.49	3.81	0.00
	GVW	11.4	2.5	4.4	38.9	18.0	36.8	46.0	21.6	60.2	72.1	52.4	68.7	105.7	0.0
S	Num	6	952	478	8	47	314	4	32	92	9	2	2	2	0
	Flex	.10	.00	.00	.65	.16	.56	.22	.11	1.09	.66	1.13	.82	.99	0.00
	Rigid	.21	.00	.00	.90	.16	1.07	.58	.13	1.94	1.55	1.08	1.15	2.18	0.00
	GVW	15.5	2.5	4.0	35.6	15.4	38.7	45.7	22.1	65.1	74.6	57.6	63.2	95.0	0.0
N Lane1	Num	4	998	505	10	58	268	3	43	73	10	1	2	2	0
	Flex	.02	.00	.00	.82	.31	.46	.25	.11	.99	.60	.73	1.12	2.01	0.00
	Rigid	.04	.00	.00	1.09	.31	.87	.69	.12	1.65	1.40	1.00	1.49	3.81	0.00
	GVW	11.4	2.5	4.4	38.9	18.0	36.8	46.0	21.6	60.2	72.1	52.4	68.7	105.7	0.0
S Lane1	Num	6	952	478	8	47	314	4	32	92	9	2	2	2	0
	Flex	.10	.00	.00	.65	.16	.56	.22	.11	1.09	.66	1.13	.82	.99	0.00
	Rigid	.21	.00	.00	.90	.16	1.07	.58	.13	1.94	1.55	1.08	1.15	2.18	0.00
	GVW	15.5	2.5	4.0	35.6	15.4	38.7	45.7	22.1	65.1	74.6	57.6	63.2	95.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9