

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	2,495	1,211	21	116	553	4	104	200	14	2	4	4	0
	Flex	.05	.00	.00	.86	.32	.59	.52	.10	1.21	.96	1.46	.61	1.75	0.00
	Rigid	.10	.01	.00	1.17	.33	1.14	1.27	.12	2.16	2.27	1.56	.80	3.95	0.00
	GVW	14.5	2.7	4.5	36.6	17.8	37.6	51.6	20.7	63.5	79.2	52.6	57.6	113.7	0.0
N	Num	4	1,259	590	9	48	260	2	45	75	8	2	2	2	0
	Flex	.05	.00	.00	.79	.36	.50	.36	.09	1.04	1.09	.22	.78	2.24	0.00
	Rigid	.11	.00	.00	1.12	.37	.96	1.08	.10	1.77	2.64	.25	.94	5.69	0.00
	GVW	12.9	2.5	4.4	37.5	17.9	35.9	51.5	19.3	59.8	82.2	31.6	61.6	127.9	0.0
S	Num	11	1,236	621	12	68	292	3	60	125	6	1	2	2	0
	Flex	.04	.01	.00	.89	.29	.66	.56	.12	1.32	.87	1.92	.64	1.47	0.00
	Rigid	.09	.01	.00	1.19	.29	1.31	1.31	.13	2.41	2.01	2.08	.83	2.61	0.00
	GVW	14.9	2.9	4.6	35.9	17.7	39.0	51.7	21.8	65.9	76.5	59.7	58.4	102.1	0.0
N Lane1	Num	4	1,259	590	9	48	260	2	45	75	8	2	2	2	0
	Flex	.05	.00	.00	.79	.36	.50	.36	.09	1.04	1.09	.22	.78	2.24	0.00
	Rigid	.11	.00	.00	1.12	.37	.96	1.08	.10	1.77	2.64	.25	.94	5.69	0.00
	GVW	12.9	2.5	4.4	37.5	17.9	35.9	51.5	19.3	59.8	82.2	31.6	61.6	127.9	0.0
S Lane1	Num	11	1,236	621	12	68	292	3	60	125	6	1	2	2	0
	Flex	.04	.01	.00	.89	.29	.66	.56	.12	1.32	.87	1.92	.64	1.47	0.00
	Rigid	.09	.01	.00	1.19	.29	1.31	1.31	.13	2.41	2.01	2.08	.83	2.61	0.00
	GVW	14.9	2.9	4.6	35.9	17.7	39.0	51.7	21.8	65.9	76.5	59.7	58.4	102.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00192
County: Twin Falls
Funct Class: R Principal Arterial - Other
Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
Daily Factor Grp: 5
Axle Factor Grp: 2
Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9