

Idaho Transportation Department

Monthly WIM Distribution for Aug-2024

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	2,343	1,154	21	110	548	4	91	198	14	1	4	5	0
	Flex	.05	.00	.00	.96	.34	.60	.45	.12	1.26	.89	.83	.88	1.70	0.00
	Rigid	.10	.00	.00	1.36	.35	1.16	1.19	.14	2.25	2.12	.94	1.32	3.32	0.00
	GVW	14.2	2.7	4.5	38.3	17.9	37.4	50.9	21.4	64.1	76.0	50.2	61.4	100.1	0.0
N	Num	4	1,165	560	9	45	250	2	36	73	7	1	2	3	0
	Flex	.05	.00	.00	1.01	.37	.53	.48	.12	1.15	.98	2.11	.89	1.91	0.00
	Rigid	.11	.00	.00	1.46	.39	1.01	1.36	.13	1.97	2.38	2.15	1.20	3.59	0.00
	GVW	13.4	2.5	4.4	38.5	18.0	35.8	53.7	20.4	60.5	80.8	56.6	59.6	103.3	0.0
S	Num	11	1,177	594	12	65	297	3	54	126	7	1	3	3	0
	Flex	.04	.00	.00	.89	.31	.67	.49	.13	1.33	.65	.87	.60	1.42	0.00
	Rigid	.09	.00	.00	1.22	.32	1.31	1.20	.15	2.43	1.50	.99	1.02	2.56	0.00
	GVW	14.4	2.8	4.6	37.3	17.9	38.9	50.3	22.2	66.3	68.1	53.0	60.4	91.3	0.0
N Lane1	Num	4	1,165	560	9	45	250	2	36	73	7	1	2	3	0
	Flex	.05	.00	.00	1.01	.37	.53	.48	.12	1.15	.98	2.11	.89	1.91	0.00
	Rigid	.11	.00	.00	1.46	.39	1.01	1.36	.13	1.97	2.38	2.15	1.20	3.59	0.00
	GVW	13.4	2.5	4.4	38.5	18.0	35.8	53.7	20.4	60.5	80.8	56.6	59.6	103.3	0.0
S Lane1	Num	11	1,177	594	12	65	297	3	54	126	7	1	3	3	0
	Flex	.04	.00	.00	.89	.31	.67	.49	.13	1.33	.65	.87	.60	1.42	0.00
	Rigid	.09	.00	.00	1.22	.32	1.31	1.20	.15	2.43	1.50	.99	1.02	2.56	0.00
	GVW	14.4	2.8	4.6	37.3	17.9	38.9	50.3	22.2	66.3	68.1	53.0	60.4	91.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2024

Site names: 00192

County: Twin Falls

Funct Class: R Principal Arterial - Other

Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3

Daily Factor Grp: 5

Axle Factor Grp: 2

Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9