

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	1,919	1,039	20	109	615	10	88	166	18	1	3	3	0
	Flex	.08	.00	.00	.77	.19	.50	.23	.11	1.01	.64	.60	.97	1.15	0.00
	Rigid	.17	.00	.00	.99	.19	.95	.61	.13	1.74	1.50	.83	1.22	2.49	0.00
	GVW	15.1	2.4	4.1	37.3	16.3	37.6	44.8	22.4	62.1	73.1	46.7	67.7	101.6	0.0
N	Num	4	929	476	7	41	260	6	30	66	9	1	2	2	0
	Flex	.05	.00	.00	.60	.16	.42	.22	.10	.87	.65	.54	1.04	1.15	0.00
	Rigid	.10	.00	.00	.78	.16	.76	.67	.11	1.45	1.55	.85	1.30	2.53	0.00
	GVW	13.8	2.3	4.0	35.5	15.3	36.1	45.0	21.2	59.1	75.4	48.2	68.8	103.4	0.0
S	Num	6	990	562	13	68	355	5	58	100	9	2	2	2	0
	Flex	.11	.00	.00	.86	.21	.57	.25	.12	1.11	.64	.54	.89	1.18	0.00
	Rigid	.23	.00	.00	1.09	.20	1.08	.64	.14	1.93	1.46	.53	1.14	2.34	0.00
	GVW	16.2	2.5	4.2	38.1	16.9	38.8	44.9	23.0	64.2	70.5	37.1	65.3	97.8	0.0
N Lane1	Num	4	929	476	7	41	260	6	30	66	9	1	2	2	0
	Flex	.05	.00	.00	.60	.16	.42	.22	.10	.87	.65	.54	1.04	1.15	0.00
	Rigid	.10	.00	.00	.78	.16	.76	.67	.11	1.45	1.55	.85	1.30	2.53	0.00
	GVW	13.8	2.3	4.0	35.5	15.3	36.1	45.0	21.2	59.1	75.4	48.2	68.8	103.4	0.0
S Lane1	Num	6	990	562	13	68	355	5	58	100	9	2	2	2	0
	Flex	.11	.00	.00	.86	.21	.57	.25	.12	1.11	.64	.54	.89	1.18	0.00
	Rigid	.23	.00	.00	1.09	.20	1.08	.64	.14	1.93	1.46	.53	1.14	2.34	0.00
	GVW	16.2	2.5	4.2	38.1	16.9	38.8	44.9	23.0	64.2	70.5	37.1	65.3	97.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00192
County: Twin Falls
Funct Class: R Principal Arterial - Other
Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
Daily Factor Grp: 5
Axle Factor Grp: 2
Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9