

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	24	2,156	1,116	29	137	191	9	91	706	51	5	7	20	0
	Flex	.03	.00	.00	.79	.29	.35	.20	.14	.85	.59	1.03	.92	1.47	0.00
	Rigid	.07	.00	.00	.95	.29	.63	.50	.16	1.55	1.40	1.01	1.33	2.11	0.00
	GVW	12.8	2.6	4.5	34.1	18.4	33.4	42.4	23.5	62.4	75.4	54.2	64.6	89.4	0.0
N	Num	10	1,145	609	17	81	89	7	55	324	35	4	3	10	0
	Flex	.04	.00	.00	.79	.37	.39	.15	.13	.94	.68	1.22	1.00	1.79	0.00
	Rigid	.08	.00	.00	.99	.37	.70	.40	.14	1.68	1.64	1.18	1.38	2.63	0.00
	GVW	13.0	2.6	4.6	35.4	19.5	33.9	40.1	22.7	62.8	77.6	56.4	62.3	95.6	0.0
S	Num	14	1,011	506	12	56	102	3	36	382	17	3	4	9	0
	Flex	.03	.00	.00	.78	.18	.32	.26	.17	.79	.45	.88	.90	1.18	0.00
	Rigid	.07	.00	.00	.90	.17	.57	.56	.19	1.44	1.04	.90	1.32	1.62	0.00
	GVW	12.7	2.7	4.4	32.5	16.8	33.0	43.3	24.6	62.1	71.1	53.6	67.3	83.8	0.0
N Lane1	Num	10	1,145	609	17	81	89	7	55	324	35	4	3	10	0
	Flex	.04	.00	.00	.79	.37	.39	.15	.13	.94	.68	1.22	1.00	1.79	0.00
	Rigid	.08	.00	.00	.99	.37	.70	.40	.14	1.68	1.64	1.18	1.38	2.63	0.00
	GVW	13.0	2.6	4.6	35.4	19.5	33.9	40.1	22.7	62.8	77.6	56.4	62.3	95.6	0.0
S Lane1	Num	14	1,011	506	12	56	102	3	36	382	17	3	4	9	0
	Flex	.03	.00	.00	.78	.18	.32	.26	.17	.79	.45	.88	.90	1.18	0.00
	Rigid	.07	.00	.00	.90	.17	.57	.56	.19	1.44	1.04	.90	1.32	1.62	0.00
	GVW	12.7	2.7	4.4	32.5	16.8	33.0	43.3	24.6	62.1	71.1	53.6	67.3	83.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00192
 County: Twin Falls
 Funct Class: R Principal Arterial - Other
 Location: US-93 1 Mi. S of Rogerson Rd

Seasonal Factor Grp: 3
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9