

Idaho Transportation Department

Monthly WIM Distribution for Feb-2015

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	3,916	2,397	56	228	18	3	14	98	70	2	1	21	0
	Flex	.00	.00	.00	.43	.11	.24	.19	.24	.49	.30	.78	.47	.48	0.00
	Rigid	.00	.00	.00	.48	.12	.33	.37	.26	.80	.59	.78	.49	.87	0.00
	GVW	2.5	3.8	5.7	20.6	14.1	23.7	38.8	25.2	46.0	52.5	42.7	48.9	64.6	0.0
E	Num	2	2,106	1,211	20	30	12	3	8	61	48	2	1	10	0
	Flex	.00	.00	.00	.11	.08	.13	.12	.12	.22	.15	.30	.52	.19	0.00
	Rigid	.00	.00	.00	.11	.07	.17	.21	.12	.34	.28	.29	.55	.33	0.00
	GVW	3.0	3.1	5.2	17.2	14.8	22.0	34.8	24.5	41.8	45.5	39.6	49.7	49.7	0.0
W	Num	3	1,810	1,185	36	198	8	1	7	37	22	1	1	12	0
	Flex	.00	.00	.00	.62	.12	.56	.44	.37	.98	.68	.79	.24	.67	0.00
	Rigid	.00	.00	.00	.69	.13	.77	.94	.40	1.59	1.40	.80	.24	1.24	0.00
	GVW	2.2	4.6	6.2	22.6	14.1	29.2	47.7	25.5	52.9	71.7	35.5	42.6	74.6	0.0
E Lane1	Num	2	2,106	1,211	20	30	12	3	8	61	48	2	1	10	0
	Flex	.00	.00	.00	.11	.08	.13	.12	.12	.22	.15	.30	.52	.19	0.00
	Rigid	.00	.00	.00	.11	.07	.17	.21	.12	.34	.28	.29	.55	.33	0.00
	GVW	3.0	3.1	5.2	17.2	14.8	22.0	34.8	24.5	41.8	45.5	39.6	49.7	49.7	0.0
W Lane1	Num	3	1,810	1,185	36	198	8	1	7	37	22	1	1	12	0
	Flex	.00	.00	.00	.62	.12	.56	.44	.37	.98	.68	.79	.24	.67	0.00
	Rigid	.00	.00	.00	.69	.13	.77	.94	.40	1.59	1.40	.80	.24	1.24	0.00
	GVW	2.2	4.6	6.2	22.6	14.1	29.2	47.7	25.5	52.9	71.7	35.5	42.6	74.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2015

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9