

Idaho Transportation Department

Monthly WIM Distribution for May-2015

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	27	5,129	2,982	72	178	67	21	28	220	144	3	2	46	0
	Flex	.00	.00	.00	.35	.12	.39	.21	.23	.55	.34	.58	.43	.49	0.00
	Rigid	.00	.00	.00	.38	.12	.52	.49	.24	.92	.75	.56	.43	.98	0.00
	GVW	1.9	3.3	5.8	22.3	15.5	28.3	44.2	27.2	49.6	61.9	45.9	51.1	67.4	0.0
E	Num	13	2,617	1,508	31	65	29	18	15	107	71	2	1	17	0
	Flex	.00	.00	.00	.23	.10	.20	.16	.22	.27	.18	.45	.52	.30	0.00
	Rigid	.00	.00	.00	.24	.10	.26	.38	.23	.44	.37	.43	.52	.58	0.00
	GVW	2.2	3.1	5.4	20.2	15.4	24.9	42.5	27.2	44.4	50.4	43.6	54.8	62.4	0.0
W	Num	14	2,512	1,474	41	114	40	4	14	113	73	2	2	29	0
	Flex	.00	.00	.00	.45	.13	.55	.53	.24	.80	.49	.72	.36	.58	0.00
	Rigid	.00	.00	.00	.50	.13	.76	1.37	.25	1.36	1.11	.69	.37	1.20	0.00
	GVW	1.6	3.6	6.1	23.9	15.5	31.2	57.0	27.4	54.4	73.0	47.8	48.0	69.8	0.0
E Lane1	Num	13	2,617	1,508	31	65	29	18	15	107	71	2	1	17	0
	Flex	.00	.00	.00	.23	.10	.20	.16	.22	.27	.18	.45	.52	.30	0.00
	Rigid	.00	.00	.00	.24	.10	.26	.38	.23	.44	.37	.43	.52	.58	0.00
	GVW	2.2	3.1	5.4	20.2	15.4	24.9	42.5	27.2	44.4	50.4	43.6	54.8	62.4	0.0
W Lane1	Num	14	2,512	1,474	41	114	40	4	14	113	73	2	2	29	0
	Flex	.00	.00	.00	.45	.13	.55	.53	.24	.80	.49	.72	.36	.58	0.00
	Rigid	.00	.00	.00	.50	.13	.76	1.37	.25	1.36	1.11	.69	.37	1.20	0.00
	GVW	1.6	3.6	6.1	23.9	15.5	31.2	57.0	27.4	54.4	73.0	47.8	48.0	69.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2015

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9