

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	43	8,572	4,313	11	270	130	50	133	241	175	2	5	51	0
	Flex	.01	.00	.00	.80	.35	.56	.49	.25	.82	.61	2.03	.88	.96	0.00
	Rigid	.03	.00	.00	1.02	.34	.95	1.00	.29	1.54	1.57	2.00	1.12	1.97	0.00
	GVW	4.6	3.5	5.5	32.1	19.2	36.5	55.9	24.9	60.2	79.2	66.3	62.6	85.0	0.0
E	Num	19	3,717	2,253	4	126	58	38	62	123	86	1	3	25	0
	Flex	.01	.00	.00	.85	.41	.66	.54	.27	.95	.62	2.29	.89	1.37	0.00
	Rigid	.03	.00	.00	1.16	.41	1.13	.99	.32	1.81	1.52	2.27	1.18	2.89	0.00
	GVW	5.8	2.8	4.9	34.9	20.1	37.9	55.3	25.0	62.4	73.6	68.6	65.8	101.6	0.0
W	Num	24	4,855	2,060	7	144	72	13	71	118	90	1	3	27	0
	Flex	.02	.00	.01	.71	.30	.44	.39	.23	.68	.59	1.60	.90	.58	0.00
	Rigid	.04	.00	.01	.84	.29	.72	.91	.26	1.26	1.60	1.54	1.08	1.16	0.00
	GVW	3.4	4.1	6.3	30.0	18.5	34.7	54.4	24.9	57.9	85.0	63.0	59.6	70.3	0.0
E Lane1	Num	19	3,717	2,253	4	126	58	38	62	123	86	1	3	25	0
	Flex	.01	.00	.00	.85	.41	.66	.54	.27	.95	.62	2.29	.89	1.37	0.00
	Rigid	.03	.00	.00	1.16	.41	1.13	.99	.32	1.81	1.52	2.27	1.18	2.89	0.00
	GVW	5.8	2.8	4.9	34.9	20.1	37.9	55.3	25.0	62.4	73.6	68.6	65.8	101.6	0.0
W Lane1	Num	24	4,855	2,060	7	144	72	13	71	118	90	1	3	27	0
	Flex	.02	.00	.01	.71	.30	.44	.39	.23	.68	.59	1.60	.90	.58	0.00
	Rigid	.04	.00	.01	.84	.29	.72	.91	.26	1.26	1.60	1.54	1.08	1.16	0.00
	GVW	3.4	4.1	6.3	30.0	18.5	34.7	54.4	24.9	57.9	85.0	63.0	59.6	70.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9