

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	70	10,876	4,929	10	248	127	44	161	241	163	2	6	57	0
	Flex	.01	.00	.00	.64	.33	.49	.45	.18	.69	.53	1.46	.74	.80	0.00
	Rigid	.01	.00	.00	.82	.32	.81	.93	.21	1.30	1.34	1.43	.97	1.66	0.00
	GVW	2.5	3.3	5.2	32.7	19.3	35.4	54.1	22.6	58.0	75.8	57.9	60.9	80.9	0.0
E	Num	28	4,552	2,448	5	116	54	33	78	121	80	1	3	28	0
	Flex	.01	.00	.00	.86	.44	.65	.62	.24	.95	.66	2.20	1.42	1.23	0.00
	Rigid	.03	.00	.00	1.12	.43	1.10	1.22	.28	1.84	1.66	2.17	1.84	2.60	0.00
	GVW	4.1	3.1	5.1	33.1	20.1	37.5	56.8	23.1	62.7	76.4	67.5	70.0	97.5	0.0
W	Num	43	6,324	2,481	6	132	72	14	84	119	83	2	4	29	0
	Flex	.00	.00	.00	.43	.23	.36	.27	.13	.42	.38	.98	.51	.38	0.00
	Rigid	.00	.00	.00	.55	.21	.56	.60	.15	.75	.96	.93	.61	.75	0.00
	GVW	1.3	3.4	5.3	32.1	18.6	33.5	50.7	22.2	53.1	74.6	53.1	59.1	65.2	0.0
E Lane1	Num	28	4,552	2,448	5	116	54	33	78	121	80	1	3	28	0
	Flex	.01	.00	.00	.86	.44	.65	.62	.24	.95	.66	2.20	1.42	1.23	0.00
	Rigid	.03	.00	.00	1.12	.43	1.10	1.22	.28	1.84	1.66	2.17	1.84	2.60	0.00
	GVW	4.1	3.1	5.1	33.1	20.1	37.5	56.8	23.1	62.7	76.4	67.5	70.0	97.5	0.0
W Lane1	Num	43	6,324	2,481	6	132	72	14	84	119	83	2	4	29	0
	Flex	.00	.00	.00	.43	.23	.36	.27	.13	.42	.38	.98	.51	.38	0.00
	Rigid	.00	.00	.00	.55	.21	.56	.60	.15	.75	.96	.93	.61	.75	0.00
	GVW	1.3	3.4	5.3	32.1	18.6	33.5	50.7	22.2	53.1	74.6	53.1	59.1	65.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9