Idaho Transportation Department

Monthly WIM Distribution for Sep-2024

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	47	9,159	4,559	12	276	134	53	151	255	189	1	6	54	0
	Flex	.01	.00	.00	.66	.35	.57	.54	.25	.85	.64	1.65	.75	1.15	0.00
	Rigid	.03	.00	.00	.79	.34	.93	1.13	.30	1.62	1.68	1.77	.96	2.33	0.00
	GVW	3.4	3.6	5.6	29.7	19.3	36.4	58.4	24.8	61.0	81.8	65.7	62.1	86.6	0.0
E	Num	19	3,871	2,336	5	125	60	36	61	131	90	1	4	25	0
	Flex	.02	.00	.00	.79	.40	.67	.58	.31	.99	.70	2.34	.86	1.68	0.00
	Rigid	.03	.00	.00	1.01	.40	1.09	1.13	.37	1.91	1.79	2.64	1.07	3.50	0.00
	GVW	4.4	2.9	5.0	31.3	19.8	37.2	57.9	25.4	62.6	77.5	73.1	62.6	101.6	0.0
W	Num	28	5,288	2,222	8	151	74	17	90	123	99	1	3	29	0
	Flex	.01	.00	.01	.60	.31	.50	.44	.21	.71	.58	.91	.75	.68	0.00
	Rigid	.03	.00	.01	.71	.30	.81	1.05	.25	1.32	1.59	.86	.95	1.32	0.00
	GVW	2.7	4.1	6.3	29.5	18.9	35.7	58.6	24.5	59.3	85.7	55.8	62.2	72.9	0.0
E Lane1	Num	19	3,871	2,336	5	125	60	36	61	131	90	1	4	25	0
	Flex	.02	.00	.00	.79	.40	.67	.58	.31	.99	.70	2.34	.86	1.68	0.00
	Rigid	.03	.00	.00	1.01	.40	1.09	1.13	.37	1.91	1.79	2.64	1.07	3.50	0.00
	GVW	4.4	2.9	5.0	31.3	19.8	37.2	57.9	25.4	62.6	77.5	73.1	62.6	101.6	0.0
W Lane1	Num	28	5,288	2,222	8	151	74	17	90	123	99	1	3	29	0
	Flex	.01	.00	.01	.60	.31	.50	.44	.21	.71	.58	.91	.75	.68	0.00
	Rigid	.03	.00	.01	.71	.30	.81	1.05	.25	1.32	1.59	.86	.95	1.32	0.00
	GVW	2.7	4.1	6.3	29.5	18.9	35.7	58.6	24.5	59.3	85.7	55.8	62.2	72.9	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 10/03/2024 1:40 PM

Idaho Transportation Department

Monthly WIM Distribution for Sep-2024

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 10/03/2024 1:40 PM