

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	7,554	3,807	10	224	112	45	93	218	162	1	4	40	0
	Flex	.06	.00	.01	.72	.31	.50	.51	.31	.89	.65	1.55	1.16	.96	0.00
	Rigid	.14	.00	.01	1.01	.30	.81	1.04	.36	1.68	1.72	1.51	1.38	2.02	0.00
	GVW	9.8	4.0	5.9	33.1	18.7	36.5	61.0	28.5	62.8	83.8	55.0	70.2	89.5	0.0
E	Num	3	3,315	2,066	3	98	51	32	38	115	81	1	3	20	0
	Flex	.02	.00	.00	.75	.35	.48	.58	.33	.91	.65	2.26	1.59	1.21	0.00
	Rigid	.04	.00	.00	1.11	.34	.75	1.18	.38	1.72	1.61	2.21	1.88	2.59	0.00
	GVW	9.2	2.9	4.8	35.5	19.6	35.9	63.2	29.6	64.2	76.9	68.8	76.9	102.1	0.0
W	Num	5	4,239	1,741	7	126	61	13	55	103	81	1	2	20	0
	Flex	.07	.00	.01	.70	.28	.53	.40	.29	.86	.66	1.47	.69	.69	0.00
	Rigid	.16	.00	.01	.97	.27	.89	.92	.34	1.62	1.86	1.43	.84	1.41	0.00
	GVW	8.9	4.8	7.2	31.7	18.0	37.2	58.6	27.8	61.2	90.6	52.5	61.8	76.0	0.0
E Lane1	Num	3	3,315	2,066	3	98	51	32	38	115	81	1	3	20	0
	Flex	.02	.00	.00	.75	.35	.48	.58	.33	.91	.65	2.26	1.59	1.21	0.00
	Rigid	.04	.00	.00	1.11	.34	.75	1.18	.38	1.72	1.61	2.21	1.88	2.59	0.00
	GVW	9.2	2.9	4.8	35.5	19.6	35.9	63.2	29.6	64.2	76.9	68.8	76.9	102.1	0.0
W Lane1	Num	5	4,239	1,741	7	126	61	13	55	103	81	1	2	20	0
	Flex	.07	.00	.01	.70	.28	.53	.40	.29	.86	.66	1.47	.69	.69	0.00
	Rigid	.16	.00	.01	.97	.27	.89	.92	.34	1.62	1.86	1.43	.84	1.41	0.00
	GVW	8.9	4.8	7.2	31.7	18.0	37.2	58.6	27.8	61.2	90.6	52.5	61.8	76.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9