Idaho Transportation Department

Monthly WIM Distribution for Dec-2024

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	7,468	3,638	9	215	85	24	79	200	130	2	5	34	0
	Flex	.03	.00	.01	.69	.29	.48	.54	.32	.87	.62	2.37	1.08	.88	0.00
	Rigid	.05	.00	.01	.89	.28	.79	.99	.38	1.66	1.65	2.34	1.22	1.81	0.00
	GVW	8.6	4.0	5.9	31.7	18.3	35.8	61.1	29.1	62.5	83.0	69.5	67.7	86.4	0.0
E	Num	3	3,349	1,990	3	93	39	22	34	107	66	1	2	18	0
	Flex	.03	.00	.00	.76	.34	.48	.53	.38	.91	.55	2.09	1.81	1.11	0.00
	Rigid	.06	.00	.00	1.13	.33	.75	.90	.44	1.74	1.36	2.02	2.04	2.34	0.00
	GVW	10.8	2.9	4.7	38.1	19.5	35.7	57.9	31.6	64.1	73.3	68.7	78.0	98.9	0.0
W	Num	4	4,119	1,648	7	122	46	7	47	92	64	2	3	18	0
	Flex	.02	.00	.01	.65	.26	.49	.55	.30	.82	.66	2.00	.56	.64	0.00
	Rigid	.04	.00	.01	.77	.25	.82	1.07	.35	1.56	1.91	1.97	.63	1.28	0.00
	GVW	6.9	4.8	7.2	28.6	17.4	36.0	62.8	28.0	60.6	92.0	64.9	59.1	73.5	0.0
E Lane1	Num	3	3,349	1,990	3	93	39	22	34	107	66	1	2	18	0
	Flex	.03	.00	.00	.76	.34	.48	.53	.38	.91	.55	2.09	1.81	1.11	0.00
	Rigid	.06	.00	.00	1.13	.33	.75	.90	.44	1.74	1.36	2.02	2.04	2.34	0.00
	GVW	10.8	2.9	4.7	38.1	19.5	35.7	57.9	31.6	64.1	73.3	68.7	78.0	98.9	0.0
W Lane1	Num	4	4,119	1,648	7	122	46	7	47	92	64	2	3	18	0
	Flex	.02	.00	.01	.65	.26	.49	.55	.30	.82	.66	2.00	.56	.64	0.00
	Rigid	.04	.00	.01	.77	.25	.82	1.07	.35	1.56	1.91	1.97	.63	1.28	0.00
	GVW	6.9	4.8	7.2	28.6	17.4	36.0	62.8	28.0	60.6	92.0	64.9	59.1	73.5	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 01/02/2025 11:24 AM

Idaho Transportation Department

Monthly WIM Distribution for Dec-2024

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp: 4
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 01/02/2025 11:24 AM