

Idaho Transportation Department

Monthly WIM Distribution for Jan-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	6,505	3,327	9	203	73	18	70	212	155	1	5	32	0
	Flex	.05	.00	.01	.70	.29	.52	.55	.36	.90	.69	1.42	1.02	.91	0.00
	Rigid	.12	.00	.01	.85	.29	.85	1.04	.43	1.71	1.79	1.39	1.25	1.92	0.00
	GVW	11.4	4.0	6.0	30.6	18.1	37.1	58.7	30.4	62.9	84.0	52.3	69.1	88.5	0.0
E	Num	3	3,102	1,919	2	92	37	16	30	118	83	1	3	18	0
	Flex	.03	.00	.00	.85	.34	.51	.50	.41	.93	.60	2.35	1.56	1.09	0.00
	Rigid	.06	.00	.00	1.19	.33	.81	.92	.48	1.78	1.46	2.32	1.96	2.33	0.00
	GVW	13.1	2.9	4.8	38.4	19.4	36.8	59.3	32.1	64.6	75.0	69.3	78.2	98.2	0.0
W	Num	4	3,403	1,408	7	112	36	5	40	94	72	1	2	14	0
	Flex	.06	.00	.01	.64	.26	.56	.58	.33	.84	.76	.49	.76	.70	0.00
	Rigid	.14	.00	.01	.71	.25	.95	1.16	.39	1.61	2.11	.47	.91	1.42	0.00
	GVW	11.0	5.1	7.6	27.2	17.1	38.0	59.2	29.2	60.8	93.5	35.4	64.6	77.1	0.0
E Lane1	Num	3	3,102	1,919	2	92	37	16	30	118	83	1	3	18	0
	Flex	.03	.00	.00	.85	.34	.51	.50	.41	.93	.60	2.35	1.56	1.09	0.00
	Rigid	.06	.00	.00	1.19	.33	.81	.92	.48	1.78	1.46	2.32	1.96	2.33	0.00
	GVW	13.1	2.9	4.8	38.4	19.4	36.8	59.3	32.1	64.6	75.0	69.3	78.2	98.2	0.0
W Lane1	Num	4	3,403	1,408	7	112	36	5	40	94	72	1	2	14	0
	Flex	.06	.00	.01	.64	.26	.56	.58	.33	.84	.76	.49	.76	.70	0.00
	Rigid	.14	.00	.01	.71	.25	.95	1.16	.39	1.61	2.11	.47	.91	1.42	0.00
	GVW	11.0	5.1	7.6	27.2	17.1	38.0	59.2	29.2	60.8	93.5	35.4	64.6	77.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9