Idaho Transportation Department

Monthly WIM Distribution for Feb-2025

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	6,966	3,183	11	194	69	13	69	207	157	1	5	29	0
	Flex	.04	.00	.01	.57	.30	.50	.44	.39	.92	.60	.59	1.03	.95	0.00
	Rigid	.09	.00	.01	.68	.29	.83	.89	.46	1.75	1.59	.56	1.24	2.02	0.00
	GVW	10.3	4.2	6.2	27.4	18.1	36.4	53.6	30.7	63.3	81.3	43.8	68.2	88.8	0.0
E	Num	4	4,053	1,913	3	89	36	10	33	121	89	1	3	17	0
	Flex	.03	.00	.00	.69	.35	.52	.43	.45	.97	.51	1.48	1.51	1.16	0.00
	Rigid	.06	.00	.00	.85	.34	.85	.86	.53	1.85	1.23	1.41	1.85	2.54	0.00
	GVW	11.4	3.4	5.1	32.0	19.4	36.8	52.9	32.3	65.1	71.3	63.6	75.3	100.3	0.0
W	Num	7	2,913	1,270	8	105	33	4	37	87	68	1	2	11	0
	Flex	.07	.00	.01	.52	.25	.48	.40	.34	.84	.71	.50	.67	.66	0.00
	Rigid	.16	.00	.01	.61	.25	.82	.78	.40	1.60	2.04	.47	.78	1.33	0.00
	GVW	10.3	5.3	7.8	25.9	17.1	36.1	52.4	29.4	60.7	93.9	42.4	62.2	73.6	0.0
E Lane1	Num	4	4,053	1,913	3	89	36	10	33	121	89	1	3	17	0
	Flex	.03	.00	.00	.69	.35	.52	.43	.45	.97	.51	1.48	1.51	1.16	0.00
	Rigid	.06	.00	.00	.85	.34	.85	.86	.53	1.85	1.23	1.41	1.85	2.54	0.00
	GVW	11.4	3.4	5.1	32.0	19.4	36.8	52.9	32.3	65.1	71.3	63.6	75.3	100.3	0.0
W Lane1	Num	7	2,913	1,270	8	105	33	4	37	87	68	1	2	11	0
	Flex	.07	.00	.01	.52	.25	.48	.40	.34	.84	.71	.50	.67	.66	0.00
	Rigid	.16	.00	.01	.61	.25	.82	.78	.40	1.60	2.04	.47	.78	1.33	0.00
	GVW	10.3	5.3	7.8	25.9	17.1	36.1	52.4	29.4	60.7	93.9	42.4	62.2	73.6	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 03/04/2025 8:09 PM

Idaho Transportation Department

Monthly WIM Distribution for Feb-2025

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 03/04/2025 8:09 PM