

Idaho Transportation Department

Monthly WIM Distribution for Mar-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	16	7,409	3,559	11	226	95	18	90	231	175	2	5	31	0
	Flex	.04	.00	.01	.57	.32	.55	.44	.33	.92	.62	1.43	1.18	1.03	0.00
	Rigid	.08	.00	.01	.66	.31	.91	.85	.40	1.75	1.63	1.38	1.42	2.19	0.00
	GVW	7.5	4.2	6.3	27.1	18.6	37.1	50.0	28.4	63.3	81.1	56.8	69.9	91.7	0.0
E	Num	7	3,749	2,013	3	104	49	12	39	127	96	1	3	17	0
	Flex	.05	.00	.00	.69	.36	.56	.52	.36	.97	.53	1.79	1.36	1.25	0.00
	Rigid	.10	.00	.00	.84	.35	.88	.98	.44	1.85	1.29	1.74	1.58	2.64	0.00
	GVW	8.3	3.3	5.1	32.4	19.7	37.1	53.5	29.9	64.7	71.3	65.7	70.7	102.6	0.0
W	Num	9	3,660	1,546	8	122	46	7	51	104	79	1	2	14	0
	Flex	.03	.00	.01	.53	.28	.57	.39	.30	.85	.73	1.36	.89	.77	0.00
	Rigid	.07	.00	.01	.60	.28	.97	.73	.37	1.62	2.09	1.31	1.15	1.65	0.00
	GVW	6.4	5.2	7.8	25.2	17.7	37.3	44.6	27.4	61.4	93.6	56.4	65.9	78.7	0.0
E Lane1	Num	7	3,749	2,013	3	104	49	12	39	127	96	1	3	17	0
	Flex	.05	.00	.00	.69	.36	.56	.52	.36	.97	.53	1.79	1.36	1.25	0.00
	Rigid	.10	.00	.00	.84	.35	.88	.98	.44	1.85	1.29	1.74	1.58	2.64	0.00
	GVW	8.3	3.3	5.1	32.4	19.7	37.1	53.5	29.9	64.7	71.3	65.7	70.7	102.6	0.0
W Lane1	Num	9	3,660	1,546	8	122	46	7	51	104	79	1	2	14	0
	Flex	.03	.00	.01	.53	.28	.57	.39	.30	.85	.73	1.36	.89	.77	0.00
	Rigid	.07	.00	.01	.60	.28	.97	.73	.37	1.62	2.09	1.31	1.15	1.65	0.00
	GVW	6.4	5.2	7.8	25.2	17.7	37.3	44.6	27.4	61.4	93.6	56.4	65.9	78.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9