

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	38	7,928	4,156	11	256	117	39	125	250	166	2	5	45	0
	Flex	.02	.00	.01	.64	.34	.57	.57	.29	.89	.70	1.59	.93	1.04	0.00
	Rigid	.04	.00	.01	.84	.34	.93	1.14	.35	1.69	1.85	1.68	1.13	2.13	0.00
	GVW	5.3	4.0	6.1	30.7	19.0	37.2	58.4	26.8	62.0	83.7	62.1	65.8	87.6	0.0
E	Num	18	3,524	2,216	4	112	51	28	52	132	84	1	3	22	0
	Flex	.02	.00	.00	.78	.40	.56	.64	.33	1.02	.72	2.36	1.29	1.49	0.00
	Rigid	.05	.00	.00	1.08	.39	.90	1.23	.39	1.95	1.81	2.30	1.53	3.05	0.00
	GVW	5.9	3.1	5.1	38.0	20.2	36.9	59.9	27.9	64.5	77.7	70.3	73.1	103.8	0.0
W	Num	19	4,404	1,940	7	145	66	11	74	119	83	1	3	23	0
	Flex	.02	.00	.01	.55	.30	.58	.37	.27	.75	.69	1.00	.57	.61	0.00
	Rigid	.04	.00	.01	.66	.29	.97	.79	.32	1.40	1.92	1.13	.71	1.25	0.00
	GVW	4.6	4.8	7.3	25.7	18.1	37.6	49.2	26.0	59.0	89.7	55.1	56.8	72.4	0.0
E Lane1	Num	18	3,524	2,216	4	112	51	28	52	132	84	1	3	22	0
	Flex	.02	.00	.00	.78	.40	.56	.64	.33	1.02	.72	2.36	1.29	1.49	0.00
	Rigid	.05	.00	.00	1.08	.39	.90	1.23	.39	1.95	1.81	2.30	1.53	3.05	0.00
	GVW	5.9	3.1	5.1	38.0	20.2	36.9	59.9	27.9	64.5	77.7	70.3	73.1	103.8	0.0
W Lane1	Num	19	4,404	1,940	7	145	66	11	74	119	83	1	3	23	0
	Flex	.02	.00	.01	.55	.30	.58	.37	.27	.75	.69	1.00	.57	.61	0.00
	Rigid	.04	.00	.01	.66	.29	.97	.79	.32	1.40	1.92	1.13	.71	1.25	0.00
	GVW	4.6	4.8	7.3	25.7	18.1	37.6	49.2	26.0	59.0	89.7	55.1	56.8	72.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9