

Idaho Transportation Department

Monthly WIM Distribution for May-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	48	8,937	4,512	16	265	163	76	158	244	173	2	6	53	0
	Flex	.01	.00	.01	.58	.35	.57	.48	.26	.80	.65	1.15	.88	1.00	0.00
	Rigid	.02	.00	.01	.76	.34	.91	1.08	.30	1.52	1.69	1.11	1.13	2.05	0.00
	GVW	3.4	3.9	5.9	30.8	19.1	36.5	59.7	25.0	60.3	80.7	55.4	64.7	86.0	0.0
E	Num	22	3,860	2,353	5	120	58	63	65	129	83	1	4	26	0
	Flex	.01	.00	.00	.70	.41	.59	.52	.30	.96	.67	1.17	1.16	1.41	0.00
	Rigid	.03	.00	.00	.95	.40	.96	1.12	.35	1.85	1.66	1.19	1.43	2.94	0.00
	GVW	4.2	3.1	5.1	32.1	20.1	36.4	60.5	25.8	63.2	76.1	56.3	70.4	101.0	0.0
W	Num	26	5,078	2,159	11	145	105	13	94	115	90	1	3	27	0
	Flex	.01	.00	.01	.52	.30	.53	.44	.23	.62	.58	1.01	.64	.57	0.00
	Rigid	.01	.00	.01	.69	.29	.86	1.05	.27	1.13	1.59	.97	.87	1.14	0.00
	GVW	2.7	4.5	6.8	30.9	18.3	36.4	57.5	24.5	56.9	84.5	54.0	59.7	70.0	0.0
E Lane1	Num	22	3,860	2,353	5	120	58	63	65	129	83	1	4	26	0
	Flex	.01	.00	.00	.70	.41	.59	.52	.30	.96	.67	1.17	1.16	1.41	0.00
	Rigid	.03	.00	.00	.95	.40	.96	1.12	.35	1.85	1.66	1.19	1.43	2.94	0.00
	GVW	4.2	3.1	5.1	32.1	20.1	36.4	60.5	25.8	63.2	76.1	56.3	70.4	101.0	0.0
W Lane1	Num	26	5,078	2,159	11	145	105	13	94	115	90	1	3	27	0
	Flex	.01	.00	.01	.52	.30	.53	.44	.23	.62	.58	1.01	.64	.57	0.00
	Rigid	.01	.00	.01	.69	.29	.86	1.05	.27	1.13	1.59	.97	.87	1.14	0.00
	GVW	2.7	4.5	6.8	30.9	18.3	36.4	57.5	24.5	56.9	84.5	54.0	59.7	70.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9