

Idaho Transportation Department

Monthly WIM Distribution for Jun-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	65	9,488	4,803	16	286	171	77	166	264	218	2	7	55	0
	Flex	.01	.00	.00	.62	.33	.60	.53	.22	.75	.57	.94	.78	.88	0.00
	Rigid	.01	.00	.00	.80	.32	.95	1.12	.26	1.40	1.46	.91	.98	1.85	0.00
	GVW	2.8	3.8	5.9	30.7	19.0	37.2	61.0	24.3	59.3	78.4	50.3	62.3	84.0	0.0
E	Num	28	4,215	2,500	6	128	65	62	71	136	102	2	3	26	0
	Flex	.01	.00	.00	.84	.45	.73	.62	.28	.97	.68	1.40	.82	1.27	0.00
	Rigid	.02	.00	.00	1.13	.45	1.16	1.29	.33	1.86	1.68	1.35	1.05	2.74	0.00
	GVW	3.7	3.2	5.2	35.3	20.4	38.1	63.7	24.7	63.2	75.4	59.5	57.6	99.4	0.0
W	Num	38	5,272	2,303	9	158	106	15	95	128	116	1	4	29	0
	Flex	.00	.00	.01	.39	.25	.51	.33	.18	.51	.47	.35	.65	.48	0.00
	Rigid	.01	.00	.01	.47	.23	.81	.75	.21	.91	1.25	.33	.90	.92	0.00
	GVW	2.2	4.4	6.6	26.0	18.0	36.6	56.1	24.1	55.1	81.0	39.0	61.9	68.5	0.0
E Lane1	Num	28	4,215	2,500	6	128	65	62	71	136	102	2	3	26	0
	Flex	.01	.00	.00	.84	.45	.73	.62	.28	.97	.68	1.40	.82	1.27	0.00
	Rigid	.02	.00	.00	1.13	.45	1.16	1.29	.33	1.86	1.68	1.35	1.05	2.74	0.00
	GVW	3.7	3.2	5.2	35.3	20.4	38.1	63.7	24.7	63.2	75.4	59.5	57.6	99.4	0.0
W Lane1	Num	38	5,272	2,303	9	158	106	15	95	128	116	1	4	29	0
	Flex	.00	.00	.01	.39	.25	.51	.33	.18	.51	.47	.35	.65	.48	0.00
	Rigid	.01	.00	.01	.47	.23	.81	.75	.21	.91	1.25	.33	.90	.92	0.00
	GVW	2.2	4.4	6.6	26.0	18.0	36.6	56.1	24.1	55.1	81.0	39.0	61.9	68.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9