

Idaho Transportation Department

Monthly WIM Distribution for Jul-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	70	9,795	4,804	16	282	137	60	199	256	179	2	6	57	0
	Flex	.00	.00	.00	.48	.27	.45	.44	.17	.64	.46	.78	.54	.79	0.00
	Rigid	.01	.00	.00	.62	.26	.71	.96	.20	1.18	1.16	.75	.67	1.61	0.00
	GVW	2.4	3.8	5.9	28.6	18.2	34.6	57.1	22.2	57.4	74.1	44.9	56.3	81.5	0.0
E	Num	32	4,537	2,520	5	126	54	46	80	137	91	1	3	28	0
	Flex	.01	.00	.00	.68	.35	.51	.49	.22	.82	.53	1.72	.72	1.18	0.00
	Rigid	.02	.00	.00	.92	.34	.80	1.07	.26	1.55	1.28	1.68	.90	2.47	0.00
	GVW	2.7	3.1	5.0	32.5	19.3	34.8	58.7	22.4	61.2	70.8	53.9	61.3	97.8	0.0
W	Num	38	5,259	2,284	11	157	83	15	119	119	88	1	3	29	0
	Flex	.00	.00	.01	.39	.21	.42	.25	.14	.44	.38	.55	.38	.38	0.00
	Rigid	.00	.00	.01	.47	.20	.65	.58	.16	.77	1.01	.51	.48	.73	0.00
	GVW	2.1	4.4	6.7	26.4	17.3	34.5	50.0	22.1	53.1	77.4	49.6	54.0	64.0	0.0
E Lane1	Num	32	4,537	2,520	5	126	54	46	80	137	91	1	3	28	0
	Flex	.01	.00	.00	.68	.35	.51	.49	.22	.82	.53	1.72	.72	1.18	0.00
	Rigid	.02	.00	.00	.92	.34	.80	1.07	.26	1.55	1.28	1.68	.90	2.47	0.00
	GVW	2.7	3.1	5.0	32.5	19.3	34.8	58.7	22.4	61.2	70.8	53.9	61.3	97.8	0.0
W Lane1	Num	38	5,259	2,284	11	157	83	15	119	119	88	1	3	29	0
	Flex	.00	.00	.01	.39	.21	.42	.25	.14	.44	.38	.55	.38	.38	0.00
	Rigid	.00	.00	.01	.47	.20	.65	.58	.16	.77	1.01	.51	.48	.73	0.00
	GVW	2.1	4.4	6.7	26.4	17.3	34.5	50.0	22.1	53.1	77.4	49.6	54.0	64.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2025

Site names: 00241
 County: Kootenai
 Funct Class: R Principal Arterial - Other
 Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9