Idaho Transportation Department

Monthly WIM Distribution for Aug-2025

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	60	9,932	4,858	14	280	123	51	183	260	189	1	4	59	0
	Flex	.00	.00	.00	.54	.31	.57	.43	.22	.77	.55	.92	.83	.94	0.00
	Rigid	.01	.00	.00	.67	.30	.91	.90	.25	1.43	1.41	.92	1.02	1.98	0.00
	GVW	2.4	3.9	5.9	28.4	18.9	36.9	53.8	23.9	60.0	77.9	52.0	63.7	85.7	0.0
E	Num	26	4,513	2,536	5	125	57	38	75	136	91	1	2	28	0
	Flex	.01	.00	.00	.92	.40	.68	.50	.29	.97	.65	1.39	1.25	1.48	0.00
	Rigid	.01	.00	.00	1.18	.39	1.08	1.05	.34	1.84	1.62	1.34	1.70	3.22	0.00
	GVW	2.9	3.2	5.2	35.2	20.0	38.0	57.0	24.7	63.3	75.6	60.3	71.0	105.5	0.0
W	Num	34	5,419	2,322	9	155	67	13	108	125	99	1	2	31	0
	Flex	.00	.00	.01	.40	.23	.48	.27	.16	.54	.42	.49	.54	.46	0.00
	Rigid	.00	.00	.01	.48	.22	.76	.58	.19	.98	1.12	.53	.70	.89	0.00
	GVW	2.1	4.4	6.7	26.1	17.9	36.0	46.6	23.4	56.2	79.1	41.2	60.3	68.2	0.0
E Lane1	Num	26	4,513	2,536	5	125	57	38	75	136	91	1	2	28	0
	Flex	.01	.00	.00	.92	.40	.68	.50	.29	.97	.65	1.39	1.25	1.48	0.00
	Rigid	.01	.00	.00	1.18	.39	1.08	1.05	.34	1.84	1.62	1.34	1.70	3.22	0.00
	GVW	2.9	3.2	5.2	35.2	20.0	38.0	57.0	24.7	63.3	75.6	60.3	71.0	105.5	0.0
W Lane1	Num	34	5,419	2,322	9	155	67	13	108	125	99	1	2	31	0
	Flex	.00	.00	.01	.40	.23	.48	.27	.16	.54	.42	.49	.54	.46	0.00
	Rigid	.00	.00	.01	.48	.22	.76	.58	.19	.98	1.12	.53	.70	.89	0.00
	GVW	2.1	4.4	6.7	26.1	17.9	36.0	46.6	23.4	56.2	79.1	41.2	60.3	68.2	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 09/02/2025 6:57 AM

Idaho Transportation Department

Monthly WIM Distribution for Aug-2025

Site names: 00241
County: Kootenai
Funct Class: R Principal Arterial - Other
Location: SH-53 0.6 Mi. E of N Church Rd

Seasonal Factor Grp:
Daily Factor Grp: 2
Axle Factor Grp: 3
Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 09/02/2025 6:57 AM