

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	45	1,648	1,981	2	62	118	14	61	249	177	4	5	42	0
	Flex	.00	.00	.00	.71	.56	.46	.31	.29	.59	.49	.53	.35	.63	0.00
	Rigid	.00	.00	.00	1.12	.56	.76	.59	.48	1.02	1.11	.67	.42	1.10	0.00
	GVW	2.4	3.7	4.5	38.6	20.5	31.1	38.9	31.0	52.2	68.7	47.9	45.5	70.3	0.0
N	Num	29	807	971	1	30	60	9	29	121	80	3	3	21	0
	Flex	.00	.00	.00	.67	.42	.65	.30	.16	.51	.39	.33	.59	.65	0.00
	Rigid	.00	.00	.00	1.11	.42	1.13	.58	.29	.89	.80	.50	.72	1.05	0.00
	GVW	2.9	3.6	4.4	37.3	19.2	32.9	37.1	28.0	51.3	55.5	48.0	52.7	66.1	0.0
S	Num	20	1,643	1,115	2	32	62	6	32	127	97	1	3	22	0
	Flex	.00	.00	.00	.63	.67	.35	.37	.40	.65	.53	.76	.21	.76	0.00
	Rigid	.00	.00	.00	.94	.69	.53	.64	.65	1.13	1.28	.82	.23	1.33	0.00
	GVW	2.1	4.0	4.5	36.8	21.7	30.7	40.6	33.6	52.8	78.6	44.2	41.8	76.0	0.0
N Lane1	Num	29	807	971	1	30	60	9	29	121	80	3	3	21	0
	Flex	.00	.00	.00	.67	.42	.65	.30	.16	.51	.39	.33	.59	.65	0.00
	Rigid	.00	.00	.00	1.11	.42	1.13	.58	.29	.89	.80	.50	.72	1.05	0.00
	GVW	2.9	3.6	4.4	37.3	19.2	32.9	37.1	28.0	51.3	55.5	48.0	52.7	66.1	0.0
S Lane1	Num	20	1,643	1,115	2	32	62	6	32	127	97	1	3	22	0
	Flex	.00	.00	.00	.63	.67	.35	.37	.40	.65	.53	.76	.21	.76	0.00
	Rigid	.00	.00	.00	.94	.69	.53	.64	.65	1.13	1.28	.82	.23	1.33	0.00
	GVW	2.1	4.0	4.5	36.8	21.7	30.7	40.6	33.6	52.8	78.6	44.2	41.8	76.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 6
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9