

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2023

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	2,939	1,867	4	65	96	6	37	233	146	1	14	19	0
	Flex	.03	.00	.00	.43	.38	.34	.38	.37	.90	.69	.10	1.35	.98	0.00
	Rigid	.06	.00	.00	.62	.37	.59	.81	.45	1.72	1.74	.24	1.74	1.98	0.00
	GVW	12.7	2.8	4.5	27.7	20.2	33.5	48.7	31.3	63.4	81.7	43.9	73.0	90.5	0.0
N	Num	10	1,463	898	2	30	53	5	19	111	73	1	7	9	0
	Flex	.02	.00	.00	.51	.44	.39	.35	.40	.88	.64	.10	1.29	1.05	0.00
	Rigid	.04	.00	.00	.72	.43	.69	.80	.49	1.69	1.50	.24	1.71	2.02	0.00
	GVW	12.9	3.0	4.8	32.5	21.3	34.8	49.5	31.8	64.0	74.0	43.9	74.9	89.6	0.0
S	Num	2	1,476	969	2	36	44	2	18	122	72	0	8	11	0
	Flex	.16	.00	.00	.34	.34	.27	.55	.35	.91	.72	0.00	1.37	.95	0.00
	Rigid	.34	.00	.00	.47	.33	.44	1.02	.42	1.73	1.93	0.00	1.68	2.01	0.00
	GVW	12.1	2.6	4.3	24.2	19.4	31.7	54.6	31.3	62.6	89.3	0.0	70.2	91.8	0.0
N Lane1	Num	10	1,463	898	2	30	53	5	19	111	73	1	7	9	0
	Flex	.02	.00	.00	.51	.44	.39	.35	.40	.88	.64	.10	1.29	1.05	0.00
	Rigid	.04	.00	.00	.72	.43	.69	.80	.49	1.69	1.50	.24	1.71	2.02	0.00
	GVW	12.9	3.0	4.8	32.5	21.3	34.8	49.5	31.8	64.0	74.0	43.9	74.9	89.6	0.0
S Lane1	Num	2	1,476	969	2	36	44	2	18	122	72	0	8	11	0
	Flex	.16	.00	.00	.34	.34	.27	.55	.35	.91	.72	0.00	1.37	.95	0.00
	Rigid	.34	.00	.00	.47	.33	.44	1.02	.42	1.73	1.93	0.00	1.68	2.01	0.00
	GVW	12.1	2.6	4.3	24.2	19.4	31.7	54.6	31.3	62.6	89.3	0.0	70.2	91.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2023

Site names: 00319  
 County: Bonner  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9