

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	4,768	2,922	6	116	95	14	114	287	176	1	11	34	0
	Flex	.06	.00	.00	1.00	.45	.45	.52	.14	.72	.62	.56	1.25	.87	0.00
	Rigid	.12	.00	.00	1.47	.46	.74	1.05	.17	1.33	1.51	.54	1.92	1.69	0.00
	GVW	9.0	2.9	4.8	40.3	19.9	31.6	53.5	20.6	54.9	71.9	46.0	66.4	81.9	0.0
N	Num	5	2,434	1,442	4	54	46	8	55	146	96	1	7	16	0
	Flex	.05	.00	.00	1.10	.63	.61	.60	.18	.92	.77	.56	1.62	1.07	0.00
	Rigid	.11	.00	.00	1.61	.65	1.06	1.14	.20	1.73	1.83	.54	2.54	2.06	0.00
	GVW	10.0	3.0	5.1	40.7	21.2	34.7	49.6	21.1	58.0	71.9	46.0	72.0	83.1	0.0
S	Num	3	2,334	1,481	3	62	49	6	59	141	80	0	5	18	0
	Flex	.04	.00	.00	.64	.30	.26	.44	.12	.51	.43	0.00	.58	.70	0.00
	Rigid	.09	.00	.00	.94	.29	.39	.89	.14	.89	1.07	0.00	.78	1.36	0.00
	GVW	5.2	2.7	4.5	39.9	18.7	28.3	55.1	20.1	51.2	70.7	0.0	55.1	80.3	0.0
N Lane1	Num	5	2,434	1,442	4	54	46	8	55	146	96	1	7	16	0
	Flex	.05	.00	.00	1.10	.63	.61	.60	.18	.92	.77	.56	1.62	1.07	0.00
	Rigid	.11	.00	.00	1.61	.65	1.06	1.14	.20	1.73	1.83	.54	2.54	2.06	0.00
	GVW	10.0	3.0	5.1	40.7	21.2	34.7	49.6	21.1	58.0	71.9	46.0	72.0	83.1	0.0
S Lane1	Num	3	2,334	1,481	3	62	49	6	59	141	80	0	5	18	0
	Flex	.04	.00	.00	.64	.30	.26	.44	.12	.51	.43	0.00	.58	.70	0.00
	Rigid	.09	.00	.00	.94	.29	.39	.89	.14	.89	1.07	0.00	.78	1.36	0.00
	GVW	5.2	2.7	4.5	39.9	18.7	28.3	55.1	20.1	51.2	70.7	0.0	55.1	80.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9