

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	5,938	2,130	5	80	100	27	59	237	160	1	9	36	0
	Flex	.13	.00	.00	.55	.45	.44	.55	.20	.85	.75	.05	1.13	1.01	0.00
	Rigid	.28	.00	.00	.72	.45	.76	1.16	.23	1.60	1.89	.06	1.65	1.92	0.00
	GVW	15.7	3.1	4.7	26.7	20.7	32.9	63.2	25.0	60.3	81.2	25.8	66.9	88.6	0.0
N	Num	5	1,968	1,273	3	46	50	23	34	150	108	1	7	16	0
	Flex	.13	.00	.00	.49	.48	.62	.54	.23	.93	.79	.05	1.33	1.22	0.00
	Rigid	.27	.00	.00	.69	.48	1.13	1.14	.26	1.78	1.98	.05	1.99	2.35	0.00
	GVW	16.3	3.0	5.0	28.3	21.3	36.9	61.7	25.9	63.1	80.5	24.1	73.5	92.0	0.0
S	Num	2	3,970	890	3	35	53	5	26	91	58	1	4	22	0
	Flex	.13	.00	.00	.61	.37	.22	.69	.16	.63	.63	.04	1.33	.75	0.00
	Rigid	.26	.00	.00	.74	.37	.32	1.18	.18	1.13	1.64	.07	1.73	1.44	0.00
	GVW	12.7	3.2	4.3	24.1	19.4	27.4	59.6	23.1	53.5	81.6	29.1	65.6	82.9	0.0
N Lane1	Num	5	1,968	1,273	3	46	50	23	34	150	108	1	7	16	0
	Flex	.13	.00	.00	.49	.48	.62	.54	.23	.93	.79	.05	1.33	1.22	0.00
	Rigid	.27	.00	.00	.69	.48	1.13	1.14	.26	1.78	1.98	.05	1.99	2.35	0.00
	GVW	16.3	3.0	5.0	28.3	21.3	36.9	61.7	25.9	63.1	80.5	24.1	73.5	92.0	0.0
S Lane1	Num	2	3,970	890	3	35	53	5	26	91	58	1	4	22	0
	Flex	.13	.00	.00	.61	.37	.22	.69	.16	.63	.63	.04	1.33	.75	0.00
	Rigid	.26	.00	.00	.74	.37	.32	1.18	.18	1.13	1.64	.07	1.73	1.44	0.00
	GVW	12.7	3.2	4.3	24.1	19.4	27.4	59.6	23.1	53.5	81.6	29.1	65.6	82.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9