

Idaho Transportation Department

Monthly WIM Distribution for Nov-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	3,715	2,351	6	80	104	21	50	266	164	2	9	26	0
	Flex	.18	.00	.00	.58	.40	.30	.39	.23	.87	.67	.83	1.57	.93	0.00
	Rigid	.38	.00	.00	.74	.39	.49	.84	.28	1.65	1.72	.79	2.11	1.84	0.00
	GVW	15.4	2.8	4.6	26.1	20.4	31.5	52.1	27.2	62.1	81.3	52.3	77.4	87.9	0.0
N	Num	5	1,762	1,144	3	38	39	16	26	127	94	1	6	12	0
	Flex	.15	.00	.00	.45	.47	.39	.39	.26	.91	.67	.78	1.39	1.20	0.00
	Rigid	.31	.00	.00	.57	.46	.68	.86	.32	1.75	1.69	.74	2.04	2.26	0.00
	GVW	14.3	3.0	4.8	25.6	21.3	34.1	53.3	28.0	64.1	78.7	49.7	77.7	91.6	0.0
S	Num	2	1,953	1,207	4	42	65	8	25	139	70	1	5	14	0
	Flex	.32	.00	.00	.67	.34	.25	.60	.19	.80	.65	.71	2.06	.75	0.00
	Rigid	.67	.00	.00	.86	.33	.39	1.17	.23	1.50	1.69	.67	2.52	1.54	0.00
	GVW	18.3	2.7	4.3	26.4	19.6	29.8	57.7	25.9	59.7	84.0	53.4	79.4	84.6	0.0
N Lane1	Num	5	1,762	1,144	3	38	39	16	26	127	94	1	6	12	0
	Flex	.15	.00	.00	.45	.47	.39	.39	.26	.91	.67	.78	1.39	1.20	0.00
	Rigid	.31	.00	.00	.57	.46	.68	.86	.32	1.75	1.69	.74	2.04	2.26	0.00
	GVW	14.3	3.0	4.8	25.6	21.3	34.1	53.3	28.0	64.1	78.7	49.7	77.7	91.6	0.0
S Lane1	Num	2	1,953	1,207	4	42	65	8	25	139	70	1	5	14	0
	Flex	.32	.00	.00	.67	.34	.25	.60	.19	.80	.65	.71	2.06	.75	0.00
	Rigid	.67	.00	.00	.86	.33	.39	1.17	.23	1.50	1.69	.67	2.52	1.54	0.00
	GVW	18.3	2.7	4.3	26.4	19.6	29.8	57.7	25.9	59.7	84.0	53.4	79.4	84.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2023

Site names: 00319
 County: Bonner
 Funct Class: R Principal Arterial - Other
 Location: US-95 2 Mi. S of Samuels Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 9

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9